

THREE AXIS PORTIONING METHOD

Field of the Invention

This invention pertains to methods for portioning foodstuff, and more particularly, for portioning a foodstuff in accordance with a predetermined shape by
5 building a three-dimensional map of the foodstuff and then cutting the foodstuff in three dimensions.

Background of the Invention

The slaughterhouse industries have traditionally been labor intensive; however, as in other labor intensive segments of industry, attempts are being made to
10 reduce manual labor, increase speed, and improve productivity. A particularly labor intensive task is the portioning of foodstuffs such as meats from beef, poultry or fish. An important goal in food portioning is consistency. For instance, restaurants want to serve portions that will not differ markedly from day to day in size, quality, fat content and/or other criteria. In order to meet minimum weight specifications, a food
15 portion often has to exceed the acceptable minimum weight. This is because restaurants must take into account some of the variation that can exist between portions. In order to assure that all portions meet minimum specifications, it is usually necessary to use a target weight that is somewhat above the minimum. This may be a bonus to consumers but a problem for restaurateurs and others who may
20 end up giving away a significant portion of their profit margin. By having consistent portions, restaurateurs can reduce the amount of excess that is built into the portions they serve, and consumers are more likely to receive the same quantity and quality of meat product.

Up until now, skilled workers usually bore the responsibility of cutting foodstuffs into constant weight or constant sized portions. These methods can and often do result in waste. Workers, in theory, can manually portion meat to about the same size of portions. However, workers, unlike machines, fatigue and the constant repetitive motion involved with butchering may lead to disabling injuries.

Therefore, the industry is aware of the need to increase the productivity of its work, without unduly burdening its workers. Several inventors have sought to devise ways to equally portion meats utilizing automated machinery to reduce manual labor. Therefore, methods and machines have been designed in an attempt to automatically cut food so that portions are of approximately equal weight.

One approach to introduce automation into the food portioning industry is to measure the cross sectional area of the foodstuff and assume that such area remains constant throughout the length of foodstuff. As the conveyer moves forward, a transverse cutting device is activated at equally spaced predetermined time intervals. This method achieves portions of equal thickness, but not necessarily equal weight, as the cross-sectional profile of each succeeding cut can be smaller or larger than the previous one. In order to achieve substantial equal weight portions, this method requires that a human operator trim the foodstuff so that it essentially conforms to a uniform cross-section along the longitudinal axis. Once this step is performed, the machine may proceed cutting at predetermined lengths. This method could lead to a large amount of waste, and inconsistent weight portions.

An improvement over the above method can take into account the cross-sectional area after each cut is made. From this measurement and the assumed density of the foodstuff, the thickness to achieve a desired weight can be calculated by integrating the cross sectional area over the length until the desired weight is reached. As the conveyor advances, its forward progress is monitored and the foodstuff is trimmed in a transverse manner at the point when the thickness corresponds to the calculated thickness. This process is repeated until the whole foodstuff, for example, a primal cut of beef, or a fish is portioned into individualized, nearly equal weight portions. However, this method does not account for indentations, significant contours, or tissue discontinuities appearing throughout the foodstuff, which can often affect the density. Further, these methods do not contemplate cutting in three dimensions, meaning that usually one dimension is always fixed, as happens with chicken breasts or a primal cut of beef. Chicken

breasts may be portioned along the length and width, and a primal cut of beef, such as a loin, is cut lengthwise.

Other automated methods are aimed at producing food portions which trim fat to produce portions with acceptable quantities of lean meat in relation to fat. Again, with these methods, portioning is done in two dimensions. As with previous methods, the initial portioning is done by human operators to carve the initial starting block and only then, can the machine proceed. These methods can rely on a scanning apparatus to determine where the demarcations between fat, bone, or cartilage and meat lie. Scanning apparatus require light or X-ray radiation to detect the fat regions. After this determination is made, a machine can trim the fat from the lean tissue. Once the fat is removed, the resultant food portion is weighed and sorted. These methods are "after the fact," since the weight or size of the individual food portions is not considered in determining the appropriate amount of portioning. The portions are simply sorted according to weight after the trimming operation is complete.

In a variant of a previous method, other methods of portioning involve scanning the foodstuff to determine the thickness of the foodstuff passing directly underneath the scanner. From the scan, a computer will be able to mark the cutting line at which to cut to achieve the predetermined weight or size. The cutting apparatus can move while the foodstuff also moves on the conveyor, or the conveyor may stop at a cutting station and allow the cutting apparatus to cut the portion. These methods are limited in that the only cut that can be made is in the transverse direction. Using this method, one is also limited to a foodstuff portion having the initial thickness.

Other methods are directed at ways of classifying meats to determine which cut will maximize profit, i.e., which cut of meat is selling at the highest price per pound at the current time. A computer may be used to calculate and determine a portioning strategy to maximize the amount of those portions which are selling at the highest price. These methods lack the capability to generate a three-dimensional map and are concerned only with making primal cuts of meat.

Other methods are directed at increasing the speed of the cutting devices, or perhaps cutting the foodstuff in two directions. However, these methods, as with the methods previously mentioned, assume that the foodstuff is fixed in one dimension, most commonly the thickness dimension. This may be unacceptable for a variety of reasons. Heretofore, attempts have not been made to portion foodstuffs automatically along a third dimension to arrive at the desired shape or weight.

Portions of meat, particularly chicken breasts, have now increased in size so greatly that two-directional cuts simply are no longer suitable to trim the breasts down to desired portions.

Therefore, to date no method or apparatus has been devised that will build an
5 accurate three-dimensional map of the foodstuff, including the indentations and contours, that is to be portioned, then compare the map to a predetermined form, and then through the use of a computer controlled system automatically cut the foodstuff in three dimensions so as to achieve the predetermined shape or weight. The method of the present invention seeks to accomplish this task. The present invention will
10 further increase productivity in the methods for portioning foodstuffs, particularly those meats, such as beef, poultry or fish which have uneven surfaces, including indentations and contours, to achieve consistent portions.

Summary of the Invention

The present invention discloses a method for portioning foodstuffs in three
15 dimensions. A step in portioning according to the present invention includes scanning the foodstuff to be portioned. Followed by a step of generating a three dimensional map of the foodstuff. Then, comparing the generated three dimensional map of the foodstuff with the desired shape which is stored in the memory of a computer. The computer will then be able to determine the particular cutting path in
20 three dimensions in order to arrive at the predetermined shape or weight. After comparison of the generated map against the map stored in the computer memory, there follows a step of cutting in one direction to fix at least one dimension of the foodstuff. This is followed by a step of determining whether the foodstuff is within the tolerance limits to proceed with another cutting step or whether the foodstuff
25 portion has moved during the first cutting step. If the foodstuff portion has moved, the foodstuff will be scanned in a second scanning step and a second map of the foodstuff will be generated. Optionally, the scan may only include a map in two dimensions since one dimension has been fixed. Thereafter follows a step of determining the cutting path to cut the foodstuff along two dimensions to arrive at a
30 portion that has been trimmed along three dimensions.

A preferred embodiment of a method according to the present invention will include a step to scan the foodstuff to be portioned. Several apparatus are in existence which are suitable for this purpose. The preferred apparatus can use light or X-ray radiation. The radiation is attenuated or otherwise modified as it strikes the
35 foodstuff or passes through the foodstuff in a predictable manner so that a

relationship is formed between the attenuation and a physical parameter of the foodstuff. The scanner also includes a receiver portion, capable of receiving the radiation after being attenuated or modified by the foodstuff and capable of converting it into electrical signals which vary as a function of the physical parameter of the foodstuff. The signals are processed to represent a three dimensional map which accurately depicts the foodstuff in all details including the indentations, contours and discontinuities. Preferably, this step is carried out by a computer, having a CPU and a memory, capable of analyzing the signals sent by the receiver portion of the scanner. Once having created a three dimensional map, a step of comparing the three dimensional map with a map of a desired shape of the foodstuff follows. Preferably, this step is also carried out by a computer wherein the desired shape is stored in the memory of the computer. The CPU then executes a predetermined algorithm to fit the desired shape within the generated map. Having established a fit, the cutting path is marked in three dimensions. Thereafter, the foodstuff can be cut in at least one dimension to fix that one dimension, for example the thickness. The cutting device is directed by the computer according to the cutting path. Preferably, the cutting device is a high pressure water jet. After the first cutting step, a determination is made whether the foodstuff is within tolerance limits to proceed to a second cutting step. During the first cutting step, the foodstuff may have moved, thereby rendering the three dimensional map created in a previous step no longer accurate. The computer is required to know the position of the foodstuff to accurately cut the foodstuff to the desired shape. Therefore, there are limits placed on the amount of movement that can be tolerated during the first cutting step. If the tolerance limits have not been exceeded, the computer will direct the path of the next cutting step. Otherwise, a step follows wherein the foodstuff is scanned and preferably a two dimensional map is generated, preferably, by devices similar to the devices used in generating a three dimensional map. The newly generated map is again compared with the desired shape of the foodstuff. Preferably, this step is carried out by a computer wherein the desired shape is stored in a computer memory. The CPU may then execute a predetermined algorithm using any of a number of variables, such as the length, width or thickness, for determining a cutting path. Thereafter follows a step of cutting the foodstuff in at least one dimension to fix that dimension, or two dimensions, for example, the foodstuff may be cut a predetermined length and width, the thickness having already being fixed by a previous step. Therefore, the present invention achieves a desired shape from a

foodstuff portioned along three dimension. This is desirable when, for example, the original foodstuff portion is too big for an intended product.

Another embodiment of the present invention further includes a step of fitting several desired shapes into the generated map of the foodstuff, thereby maximizing the amount of foodstuff that is cut into desired shapes and minimizing the wasting of trailing portions.

A further embodiment of the present invention includes a product cut from a foodstuff using a method in accordance with the present invention. The foodstuff is cut and portioned along three dimensions including the thickness, width and length in two cutting steps.

A further embodiment of the present invention includes a product cut from a foodstuff using a method in accordance with the present invention. The desired final product has a substantially constant thickness, but the foodstuff has an arcuate shape. The foodstuff is cut and portioned along three dimensions including the thickness, width and length in two cutting steps. The product is cut from a foodstuff portion having an indentation. The cutting path used to cut the product is arcuate shaped to cut around the indentation in the foodstuff portion.

A further embodiment of the present invention includes a product cut from a foodstuff portion using a method in accordance with the present invention. The final product has a substantially constant thickness. The foodstuff is cut and portioned along three dimensions including the thickness, width and length in two cutting steps. The product is cut from a foodstuff having a undesirable constituent such as bone, cartilage or fat. The cutting path used to cut the product is skewed or at an angle.

A further embodiment of the present invention includes a plurality of final products cut from a foodstuff using a method in accordance with the present invention. The foodstuff is cut and portioned along three dimensions including the thickness, width and length in two cutting steps. The cutting paths can include multiple pass cuts through the foodstuff or partially control the depth of cutting. A plurality of products may be formed from a single foodstuff portion.

An advantage of a portioning method in accordance with the present invention is the elimination of manual labor to perform an initial slicing operation to fix one dimension of a portion of a foodstuff portion. Elimination of manual labor increases the productivity of the butchering industry.

A further advantage of a portioning method in accordance with the present invention is the savings incurred from optimizing a desired cut of meat product.

A further advantage of a portioning method in accordance with the present invention is the capability of cutting irregular shaped foodstuff portions having indentations or undesirable constituents.

Brief Description of the Drawings

5 The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

10 FIGURE 1 shows a flow diagram of the steps in a embodiment of a method in accordance with the present invention;

FIGURE 2 shows physical embodiments to perform the steps of the method of FIGURE 1.

FIGURE 3 shows physical embodiments to perform the steps of the method of FIGURE 1

15 FIGURE 4 shows physical embodiments to perform the steps of the method of FIGURE 1

FIGURE 5 shows a front elevation view of a product to be portioned using the method of FIGURE 1;

20 FIGURE 6 shows a top plan view of a product to be portioned using the method of FIGURE 1;

FIGURE 7 shows a front elevation view of another product to be portioned using the method of FIGURE 1;

FIGURE 8 shows a plan view of FIGURE 7;

25 FIGURE 9 shows a front elevation view of a further product to be portioned using the method of FIGURE 1;

FIGURE 10 shows a front elevation view of an additional product to be portioned using the method of FIGURE 1;

FIGURE 11 shows a front elevation view of a plurality of portions to be cut from a foodstuff using the method of FIGURE 1; and

30 FIGURE 12 shows a schematic view of an alternative embodiment of the present invention.

Detailed Description of the Preferred Embodiment

35 A preferred embodiment of a method for portioning foodstuffs in accordance with the present invention is shown in FIGURE 1. The method includes the step 102 of scanning the foodstuff to be portioned. Followed by the step 103 of generating a

three dimensional map of the foodstuff. Input 106 depicting a form of a predetermined shape is compared with the map, and a cutting path is determined in step 104 comparing the generated three dimensional map of the foodstuff with one or more desired shapes which are stored in the memory of a computer. Following is a step 108 of cutting the foodstuff in one direction to fix at least one dimension of the foodstuff. Followed by a decision-making step 110 of determining whether the foodstuff is within the tolerance limits or whether the foodstuff portion has moved during the first cutting step 108. If the foodstuff portion has moved during the cutting step 108, the foodstuff will be rescanned in step 112 and in step 114, a two dimensional image of the foodstuff will be generated. If the foodstuff portion has not moved, a second decision will ask whether the second cut path in two axes has also been determined. If the second cut path has been determined in an earlier step, such as step 104, the foodstuff will be portioned along a second and third axis. Otherwise, input 118 is received and a second cutting path is determined in step 116 coming from either step 116 or step 124. Thereafter follows a step 120 of cutting the foodstuff.

Referring to FIGURE 2, in a preferred embodiment of a method according to the present invention, the foodstuff portion 200 will travel on an endless conveyor system 202. An initial step in a method of portioning foodstuff in accordance with the present invention is scanning the foodstuff to be portioned as shown in FIGURE 1. Any number of foodstuffs desired to be portioned may be loaded onto the moving endless conveyor system 202. The conveyor is suited to carry the foodstuff along a processing line where it may be processed by the various apparatus used to carry out the steps of the present invention.

The conveyor belt 202 carries the foodstuff 200 underneath a first scanner system, generally denoted by 204. The scanner system 204 suitable for use in this method will have the ability to generate a three dimensional map of the foodstuffs. The principle behind the scanner system is the use of radiation, which forms a relationship with a physical parameter of the foodstuff which is being scanned. Any one of several devices are suitable for this method. Several devices in use today employ X-rays or visible light to generate an image of the foodstuff. A scanner according to the present invention will include both a generator 206 to irradiate the foodstuff to be scanned with radiation and a receiver 208 to receive the attenuated radiation. The receiver portion 208 can be integral with the generator 206. Radiation

may be electromagnetic radiation throughout the spectrum from high frequency radiation, such as X-rays, to relatively low frequency natural spectrum light.

Sub B3 7 A scanner can also include a receiver 208 to receive and detect the amount of radiation attenuated by an object. Attenuation can occur by passing through the object or by reflection from the object. When radiation passes through a foodstuff, a certain amount of radiation is absorbed by the foodstuff through which it passes, therefore there will be a relationship in the amount between the radiation sent to the foodstuff and the radiation received after it has passed through the foodstuff. The cause of absorption is believed to reside in the chemical bonds within the molecules of the foodstuff. Radiation once attenuated can be collected, and converted into a useable form. Photodiodes, for example, may be used to convert an amount of radiation in the visible range into a voltage or current signal. For X-rays, a scintillating material may be used to generate visible light capable of detection by a photodiode. This method is described in U.S. Patent No. 5,585,603 to Vogeley, Jr., which is herein incorporated by reference. Other methods teach the use of a video camera to determine the size and/or shape of a foodstuff. These methods and apparatus are described in Reissue Patent Nos. 33,851 and 33,904 to Rudy et al., which are herein incorporated by reference.

The signals generated by photodiodes can then be further processed by a computer to determine a physical quantity which is related to the amount of radiation which is detected. One such quantity may be the mass of the foodstuff. Since the scanner will presumably know the amount of radiation that was sent to the foodstuff and the amount of radiation that was received, the amount absorbed forms a difference which is a direct relationship of the mass of the foodstuff. Once knowing the mass, volume of the incremental scanned area is calculated by assuming a density. The thickness can be derived once knowing the linear dimensions of the volume.

Any one of the above-described devices currently in use today will be suitable for use in a method in accordance with the present invention. Still, other methods of three dimensional imaging may use reflective means rather than absorptive means. For example, a receiver may measure the amount of light reflected from a foodstuff rather than the amount of radiation passing through the foodstuff. The areas of foodstuff tissue are distinguishable from areas, such as the conveyor, which surround the foodstuff and have a different reflective index. These differences can be used to determine the shape of a foodstuff. A person of ordinary

skill in the art will have knowledge of suitable devices of carrying out this step in accordance with the present invention.

Using a selected method, the scanner may repeat the process in quick succeeding intervals corresponding to one incremental dimensional unit such as by
5 advancing the conveyor, or the scanner may execute a strobe-like effect, or the scanning process may be essentially continuous, with the map being formed as the foodstuff is continually advanced underneath the scanner. The imaging process can be integrated over an entire length of foodstuff to arrive at a three dimensional map of the foodstuff. The three dimensional map generated by the computer will have
10 coordinates to fixed points or locations to enable other apparatus to reference these points and trim or portion the foodstuff with reference to these fixed points accurately. Other devices for identifying fat or bony cartilaginous matter and skin may also be incorporated and adapted to the present invention. These methods are also within the scope of this invention.

Step 103 of FIGURE 1 includes generating a three dimensional map of the foodstuff from signals sent via the scanner system as described above, preferably by
15 the use of a computer 210, as shown in FIGURE 2. The computer will be capable of performing executable steps wherein the signals received by the scanner are processed by the computer to produce a three dimensional map, perhaps the map being discrete volume elements which as a whole create the three dimensional map.
20 The step of generating the three dimensional map will be followed by comparing the generated map with one or more stored maps of a desired foodstuff shape in step 104 of FIGURE 1.

Preferably, a computer 210 having a central processing unit 212 (hereinafter
25 CPU) and a memory 214 will be used in the method according to the present invention. Input 106 of FIGURE 1 of a desired shape is stored on computer memory 214. The memory can store additional maps that can readily be selected by a user via a user interface 216 when changing product lines. For instance, the user may be processing chicken breasts for a particular customer who may have a
30 particular desired shape, when the order of the customer is filled, the user may switch the mode of the computer to a different product to meet the specifications of a different customer. This switch may be automated, and triggered by a counter that keeps track of the number of foodstuff portions that have been processed or it may be carried out manually to allow the user time to retool any apparatus or recalibrate. In

other alternate embodiments of a method according to the present invention, a library of maps for a whole production plan can be stored in the memory of a computer.

John B. 17
5 In still other alternate embodiments, the computer 210 can be in communication with a network system 230 which allows the computer 210 to talk and share information with other computers. Computer 210 can also drive other peripheral hardware besides the scanner system 204. For instance, computer 210 can direct the operation of a conveyor 232, or cutting devices, generally denoted as 234. Finally, computer 210 can receive information from various sensors to guide or direct a multitude of systems.

10 In the preferred embodiment of the method of the present invention, the CPU 212 will retrieve the stored map(s), compare the stored map(s) with the generated map, and determine the path of the first cutting step 108 of FIGURE 1. The CPU will be capable of executing an algorithm wherein the algorithm has a step to select a dimensional unit for comparison. The unit may be along any linear
15 dimension or it may be a combination of linear dimensions. For example, in the preferred embodiment, thickness may be selected as the first unit of dimension to compare. If the generated map of the foodstuff is within the thickness specification of the desired shape, the computer may proceed to a further step wherein a further comparison of a different dimension is made, these comparisons may continue until it
20 is determined that the desired shape will fit within the generated map of the foodstuff. FIGURE 2 shows a foodstuff portion 200 having a desired shaped 215 fit within the dimension of the foodstuff. Thus, the computer will be able to generate one or more cutting paths to arrive at the desired shape 215 by trimming the foodstuff portion 200.

25 In an alternate embodiment, a first comparison and determination of a first unit dimension is made, if the foodstuff is within specifications of one unit dimension of the desired shape, the computer may direct the cutting devices to proceed to cut the food stuff along the predetermined cutting path to arrive at fixing one dimension. In this embodiment, having fixed one dimension, the computer can now proceed to
30 make comparisons in the remaining dimensions and cut to those dimensions accordingly in later cutting steps.

In another alternate embodiment, all comparisons are completed before cutting begins, and following a step for comparing a dimensional unit, the computer may proceed to compare the foodstuff along a second dimensional unit. For
35 example, in a preferred embodiment, the first dimensional unit for comparison is the

thickness, followed by width and then the length. However, it should be realized that dimensional comparison may proceed in any order and in any combination. Embodiments of a method in accordance with the present invention contemplates these combinations and are within the scope of this invention. The width of the
5 the desired shape being then compared to the width of the generated map. If the width of the desired shape can fit within the width of the generated shape, the computer may proceed to compare the foodstuff along a third dimensional unit. For example, if the generated map has so far met the specification for thickness and width, the computer may analyze or compare for length. In this step, the computer will compare the
10 length of the generated map to the desired shape, once the two other parameters have been established. The computer can manipulate the three dimensions individually or in combination trying to find the best fit for the desired shape into the generated map. The computer may even skew or rotate the desired shape within the generated map to avoid defects or abnormalities in the foodstuff or may adjust one dimension only.
15 The computer may also base the best fit algorithm on other considerations. For example, mass rather than size may be the determining factor. To adjust for mass, the computer will have to set two dimensions and vary the third to arrive at the desired mass or any combination of dimensions. It should also be pointed out that comparisons of dimensional units may proceed on an incremental basis, such that the
20 sum of all increments may produce a rounded or otherwise non-linear cutting path.

In determining the optimal cutting path, the computer may avoid indentations or undesired constituents such as bone or fat in the generated map to avoid having these constituents in the finished product. The devices for determining bone or fat tissue can be incorporated into to the present invention for this purpose. Other
25 embodiments may have the computer cut out or around the indentations or undesired constituents.

In still other embodiments, the desired shaped may be optimized, for instance, if longer portions are more valuable than shorter portions, yet both are acceptable to the customer, the computer may adjust the length in order to maximize the length.
30 Other units and dimensions may be selected by the computer or the user in order to maximize the value of the foodstuff portion. Dimensional units which may be used by a computer in comparison, determination and optimization step(s) include units such as length, thickness, width, or weight.

In a preferred embodiment of the method of the present invention, a cutting
35 step 108 will follow the comparison step 104 in FIGURE 1. As the foodstuff

portion 200 travels on a conveyor system 202, the conveyor 202 will have brought the foodstuff portion to a cutting station 218 as shown in FIGURE 3. The cutting device 220 will be controlled by the computer 210 with the appropriate cutting path determined in an earlier step. Preferably, the cutting device in a method according to the present invention will use a band knife or an oscillating knife if the cut to be made is a long cut, but a high pressure water jet may also be used as well, to cut the foodstuff in accordance with the directions from the computer. Such cutting devices are described in U.S. Patent No. 5,931,178 to Pfarr, which is herein incorporated by reference. Bandsaws and blades are described in U.S. Patent No. 5,937,080 to Vogeley, Jr. et al., which is herein also incorporated by reference. However, other cutting devices, such as high pressure gas or lasers, that are well known in the art may also be used.

A suitable cutting device in accordance with the present invention will be capable of cutting along one axis, preferably horizontally as shown in FIGURE 3, to establish one dimensional unit as described above. The water jet nozzle or other cutting device can be mounted on an articulating arm, such that the cutting jet may be directed at an angle or moved bi-directionally in single or multiple planes. Also, multiple cutting jets may be used together. As mentioned earlier, the computer may move the desired shape in a skewed manner to make the desired shape fit within the generated map or the computer may direct a cut be made in an arcuate or rounded configuration. The computer can also determine a cutting path to cut around bone, fat, cartilage or skin. If the desired shape is to be cut at an angle or in a arcuate fashion, a water jet may be one of the most effective ways of accomplishing this task. However, rotating or oscillating mechanical cutters using metal blades may also be used.

Alternatively, the water jet or other cutting device may make one or more passes to cut the desired thickness, or the water jet may cut from both directions. The cutting device may be mounted on a fixed platform or structure and the conveyor speed may determine the rate of portioning. Alternatively, the cutting device may be carried on a movable track system such as is disclosed in U.S. Patent No. 5,868,056 to Pfarr et al., which is herein incorporated by reference. In a movable track system, the cutting tool may move at a speed faster than the conveyor, thereby enabling more complicated and multiple pass cuts. Cutting devices may also be controlled to achieve a predetermined depth, for example when portioning a foodstuff into several products, the cutting device will need to control the depth of a cut to be able to make

several portions from a single larger portion. Any leftover portions may be retained and used for other applications or processed further or discarded.

5 In a preferred embodiment of the method of the present invention, determining whether the foodstuff portion has shifted from the fixed reference points is performed following the first cutting step in step 110 at FIGURE 1. This step will determine whether the foodstuff portion occupies the same spatial relationship after the first cutting step. Of course, after having gone through a first cutting step, the foodstuff may have been reduced in volume. Therefore, what is being determined is whether the desired portion as defined by the computer has shifted or otherwise
10 moved from its initial position. This is preferable to assuming the foodstuff portion has not moved and further processing the foodstuff portion under this assumption, resulting in an ultimate rejection or rework because the foodstuff portion had in fact moved.

FIGURE 5 shows a system 224 for determining whether the foodstuff portion
15 has shifted. The system may include such apparatus as an optical scanner, video camera, limit switches or other like apparatus for detection of out of bounds movement or motion. A person of ordinary skill in the art may readily appreciate any of a number of apparatus suitable for performing this step. In step 110, if the foodstuff is found not to have moved outside of the tolerance limits, the method
20 according to the present invention will go to another decision step 124 which will determine the need to calculate the second cutting path. It may be that the second cutting path has been determined earlier in step 104, or in the alternate embodiment where only one dimension is determined and cut in the first cutting step, it will become necessary to jump forward to a second step 116 where the computer
25 determines the second cutting path. Otherwise, from step 110 the method will jump directly to the cut portion step 120 of FIGURE 1. In step 120, the computer directs a cutting device for cutting the foodstuff in a second or third dimensional unit, such as is described above. The second cutting step 120 is represented in FIGURE 4. FIGURE 4 shows the same cutting device utilized in an earlier step, to portion the
30 foodstuff 200 in one or more axes. FIGURE 4 shows how the cutting device 220 can trim the foodstuff 200 to arrive at a second dimension, such as length, and a third dimension, such as width, to arrive at a foodstuff which has been portioned in three dimensions by one or more cutting devices. Alternatively, multiple cutting devices may be used to cut along one or more dimensions where the first cutting device is a
35 different station than the second cutting station. For example, the first cut can be

performed by a band saw or an oscillating blade and the second cut can be made by a high pressure water jet.

If the device used to detect shifting of the foodstuff signals that the foodstuff has moved from its initial position, the foodstuff portion may be rescanned in a second rescan step 112 as shown in FIGURE 1 (if step 110 utilizes a scanner, step 112 can utilize the same scanner to scan the foodstuff a second time).

In a preferred embodiment of a method in accordance with the present invention, rescanning the foodstuff may take place with similar equipment that was described for the earlier scanning step 102. FIGURE 5 shows second scanner 224 will likewise include a generator portion 226 and a receiver portion 228, which may be integral or separate devices, to be able to generate a three dimensional map of the foodstuff 200 to compare to the map stored in the computer. Step 114 uses a computer to generate another map of the foodstuff. The generated map of the foodstuff can also be described in only two dimensions, for instance, length and width, since preferably, the thickness has been established by the first cutting step. The comparison and determination of the second cutting path will be recomputed for the newly generated map of the foodstuff in step 116.

A second cutting step 120 proceeds from the second rescan step 112, map generation 114 and comparison step 116 of FIGURE 1, or this step 120 may have been jumped to from a previous step, such as the determination of whether the foodstuff was within tolerance limits in step 110. If the foodstuff has been determined to be within tolerance limits in step 110, a second decision step 124 may follow to decide whether the process jumps to step 116 or step 120. Step 124, may for instance, decide whether the cutting path has been fully described in the previous step 104, in which case, the process may proceed directly to a second cutting step 120. Alternatively, if step 104 only described the first cutting path, then the process would jump to step 116, to calculate the cut path along the second and third axis. In the second cutting step 120, the foodstuff is completed to resemble the desired shape residing within the computer memory.

Referring again to FIGURE 2, an embodiment of a foodstuff 200 to be portioned in three dimensions using a method in accordance with the present invention is shown. A conveyor 202 is suited to carry the foodstuff portion 200, such as a chicken breast, through the various steps of the method. Shown is a representative foodstuff portion 200 with the desired shape 204. A step in the method of the present invention will have generated a three dimensional map of the

chicken breast and the computer will have compared the map with the desired shape. The computer will have determined the most correct fit of the desired shape within the generated map. Shown in phantom are the cutting paths for achieving a foodstuff portion in the desired shape. The chicken breast 200 has a first, a second, and a third dimension representing thickness, width and length, respectively. In a step according to a method of the present invention, the foodstuff portion will be cut along a first path to establish one dimension, such as the thickness, as shown in FIGURE 3. It should be noted that the cutting path need not follow a linear path. The first cutting path may be an arcuate or rounded path. It should also be noted that the first cutting path may make two passes. For example, a first pass may cut along the top of the portion and a second pass will cut along the bottom of the portion. This would be desirable if the chicken breast was not lying exactly prone on the conveyor or if the chicken breast had a portion of bone or other undesirable constituent still attached to it.

A further step in a method according to the present invention will cut along a second path to establish a further dimension such as width or length or both as shown in FIGURE 4. It should be noted that the second cutting device may also move in a bi-directional manner in the same plane or in two dimensions to establish the second and third dimension. For example, the cutting device may be mounted on a moveable platform, where the cutting device may make two passes along the second dimension to shape the width, and two passes along the third dimension to shape the length. The cutting device in this step can also be the cutting device of a previous step, provided that the cutting device is able to articulate as shown in FIGURE 4, moving from the horizontal to the vertical plane. It should also be noted that these paths may not be linear but rather follow a curved or arcuate path as well. The advantage of generating a three dimensional map is that foodstuff portions may now be cut in three dimensions, whereas previously one dimension was always fixed at the start and the other two were adjusted. This is the big difference between the present invention and the prior art.

FIGURE 5 shows steps 112 and 114 of the method of the present invention. Shown is a foodstuff portion 200 which was moved from its original position, defined in phantom, to a new position. It should be noted that the chicken breast now has at least one dimension that is fixed by the first cutting step, therefore, it is only minimally required to generate a cutting path in two dimensions, such as length and width. As before, once a map is generated the map is compared to the desired shape

and the best fit is determined. This is done with the aid of a computer having a CPU and a memory. The computer can then send instructions to the appropriate peripheral devices, including cutting devices.

5 An embodiment of a foodstuff to be portioned in three dimensions using a method in accordance with the present invention is shown in FIGURE 6. FIGURE 6 shows the cutting path along two dimensions, thickness and width.

FIGURE 7 shows the same food portion as FIGURE 6 showing the length dimension. Using three axis portioning as in the method of the present invention allows for trimming the three dimensions of length, width and thickness. The first cutting step removes region 600 in FIGURE 6, while the second cutting step removes regions 700, and 702, followed by regions 704 and 706, or any combination thereof, thus achieving portioning along three axes.

Another embodiment of a foodstuff to be portioned in three dimensions using a method in accordance with the present invention is shown in FIGURE 8. FIGURE 8 shows the cutting path along two dimensions, thickness and width. However, it is to be understood that a third dimension exists and is subject to be portionable as well. First cutting step 108 may cut along line designated by 800 and 802 to remove regions 804 and 806, thus fixing one dimension. The second cutting step may cut along path 808 and 810 to remove regions 812 and 814, thus fixing two dimensions. Also shown is a cutting path following a curved or arcuate path when the foodstuff portion has indentations which would have prevented a constant thickness using conventional methods, the conventional methods only having capability to portion along two axes or two dimensions automatically. Also shown is a cutting path which can be cut by a first and second pass of the foodstuff or a cutting device having dual water jets to portion the top and the bottom simultaneously to arrive at a constant thickness for a desired shape. Alternatively, a rotating and oscillating cutting device may be used to cut the top and the bottom surfaces of the portion.

Another embodiment of a foodstuff to be portioned in three dimensions using a method in accordance with the present invention is shown in FIGURE 9. FIGURE 9 shows the cutting path along two dimensions, thickness and width, for a first and second half of a foodstuff portion. First cutting step 108 can cut along cutting paths 900 and 902 to remove regions 904 and 906, while second cutting step 120 can cut along paths 908 and 910 to remove regions 912 and 914. It should also be understood that there exists a third dimension, length, which can also be

trimmed in the second cutting step 120. Also shown is a curved cutting path which may be cut by a first and second pass of a cutting device to cut the top and bottom surfaces of the portions to arrive at a thickness for a desired shape. Alternatively, a rotating and oscillating cutting means may be used to cut the top and the bottom trailing portions.

5 *prob 6* 7 An embodiment of a foodstuff to be portioned in three dimensions using a method in accordance with the present invention is shown in FIGURE 10. FIGURE 10 shows the cutting path along two dimensions, thickness and width. First cutting step 108 can cut along cutting paths 1000 and 1002 to remove regions 1004 and 1006, while second cutting step 120 can cut along paths 1008 and 1010 to remove regions 1012 and 1014. It should also be understood that there exist a third dimension, length, which can be trimmed in the second cutting step 120. In the embodiment, a bone fragment or other undesired constituent may be avoided by skewing or rotating the desired shape within the generated shape to fit the desired shape in the generated shape, thereby avoiding the bone. The resulting cutting path is skewed or angled to avoid the undesired constituent. The cutting path to shape the thickness of the portion can be cut by a first and a second pass of the cutting device to portion the top and the bottom surfaces.

10 15 *prob 7* 20 Another embodiment of a foodstuff to be portioned in three dimensions using a method in accordance with the present invention is shown in FIGURE 11. FIGURE 11 shows the cutting path along two dimensions, thickness and width. In the embodiment, a foodstuff portion may be cut into a plurality of desired shapes. The shapes may be arranged into one generated map of the foodstuff via the use of a computer, such that the maximum amount of the foodstuff is utilized. Shown are several desired shapes to be cut from one foodstuff portion. Also shown are multiple cutting paths where several cuts are made by multiple passes of the cutting device or multiple heads. A bone fragment can also be avoided by fitting desired shapes around the bone fragment.

25 30 *ans 2* 35 FIGURE 12 schematically illustrates how a foodstuff portion 1100 may be cut to a desired thickness in accordance with the present invention. The apparatus 1101 illustrated in FIGURE 12 includes a first conveyor system 1102 for delivering foodstuff portions 1100 to the underside of a vacuum chamber 1104. The vacuum chamber is shown as including a housing 1106 in generally oblong shape having a rounded leading end portion 1107 overlying the conveyor 1102 which transitions to a substantially flat bottom section 1108 spaced above the upper rung of

the belt 1110 of the conveyor. At approximately the end of the conveyor 1102 the vacuum chamber housing extends diagonally upwardly along section 1112 to a vertical end wall 1114 of the chamber. The top surface of the chamber housing 1116 is substantially flat. A belt 1118 is trained around the top 1116, left end 1107, flat bottom 1108 and diagonal 1112 sections of the vacuum chamber housing, as well as around a drive pulley 1113 positioned outwardly adjacent the end wall 1114 of the chamber housing. The drive pulley is mounted to the wall 1114 by a bracket 1122. The drive pulley can be driven by numerous methods, for instance by an electric motor, hydraulic motor or otherwise.

A vacuum can be applied to the interior of the chamber housing 1106 by any one of numerous methods. The vacuum chamber preferably is perforated or slotted along its bottom section 1108 and the adjacent portion of the diagonal section 1112. Also the belt 1118 is preferably perforated so that suction is applied to the adjacent surface of the foodstuff 1100. Thus, foodstuff 1100 carried by conveyor 1102 becomes attached to the belt 1118 and is carried by the belt after the foodstuff portions leave the conveyor 1102, which occurs as the foodstuff portions move along the diagonal portion 1112 of the vacuum chamber. The upper surface of the foodstuff in essence adheres to the belt 1118.

The foodstuff portions 1100, being carried by the belt 1118, is trimmed to thickness by a band knife 1130, spaced beneath the diagonal section 1112 of the vacuum chamber. Rather than a band knife, another type of knife, such as an ultrasonic knife, may be utilized. The distance between the knife 1130 and the adjacent surface of the housing 1106 can be varied to adjust the thickness of the foodstuff portion 1100 as desired.

The perforations in the housing 1106, in communication with a vacuum source, do not exist past the location of the band knife 1130. Instead, pressurized air is directed through perforations in the diagonal section 1112 of a vacuum chamber housing adjacent end wall 1114, thereby to break the suction between the foodstuff portion 1100 and the belt 1118, thereby to drop the trimmed foodstuff portion onto a conveyor 1132, which then can transport the foodstuff portions to another location to be further trimmed and portioned in accordance with the present invention. As shown in FIGURE 12, a gap 1134 exists between the adjacent ends of conveyors 1102 and 1132 to allow the trim 1136 from the foodstuff to drop down away from the knife 1130.

One type of foodstuff with respect to which the present invention may be particularly useful are chicken breasts that have skin on one surface of the breasts. Preferably, such chicken breasts are placed on the conveyor 1102 with the skin side up, which is believed to provide a better suction contact with the belt 1110 than if the
5 chicken breasts were positioned skinless side up. However, it is to be understood that other types of foodstuff can be trimmed to thickness using the present invention.

While the preferred embodiment of the invention has been illustrated and described, it will be appreciated that various changes can be made therein without departing from the spirit and scope of the invention.

10

1102
1110
1112
1114
1116
1118
1120
1122
1124
1126
1128
1130
1132
1134
1136
1138
1140
1142
1144
1146
1148
1150
1152
1154
1156
1158
1160
1162
1164
1166
1168
1170
1172
1174
1176
1178
1180
1182
1184
1186
1188
1190
1192
1194
1196
1198
1200
1202
1204
1206
1208
1210
1212
1214
1216
1218
1220
1222
1224
1226
1228
1230
1232
1234
1236
1238
1240
1242
1244
1246
1248
1250
1252
1254
1256
1258
1260
1262
1264
1266
1268
1270
1272
1274
1276
1278
1280
1282
1284
1286
1288
1290
1292
1294
1296
1298
1300
1302
1304
1306
1308
1310
1312
1314
1316
1318
1320
1322
1324
1326
1328
1330
1332
1334
1336
1338
1340
1342
1344
1346
1348
1350
1352
1354
1356
1358
1360
1362
1364
1366
1368
1370
1372
1374
1376
1378
1380
1382
1384
1386
1388
1390
1392
1394
1396
1398
1400
1402
1404
1406
1408
1410
1412
1414
1416
1418
1420
1422
1424
1426
1428
1430
1432
1434
1436
1438
1440
1442
1444
1446
1448
1450
1452
1454
1456
1458
1460
1462
1464
1466
1468
1470
1472
1474
1476
1478
1480
1482
1484
1486
1488
1490
1492
1494
1496
1498
1500
1502
1504
1506
1508
1510
1512
1514
1516
1518
1520
1522
1524
1526
1528
1530
1532
1534
1536
1538
1540
1542
1544
1546
1548
1550
1552
1554
1556
1558
1560
1562
1564
1566
1568
1570
1572
1574
1576
1578
1580
1582
1584
1586
1588
1590
1592
1594
1596
1598
1600
1602
1604
1606
1608
1610
1612
1614
1616
1618
1620
1622
1624
1626
1628
1630
1632
1634
1636
1638
1640
1642
1644
1646
1648
1650
1652
1654
1656
1658
1660
1662
1664
1666
1668
1670
1672
1674
1676
1678
1680
1682
1684
1686
1688
1690
1692
1694
1696
1698
1700
1702
1704
1706
1708
1710
1712
1714
1716
1718
1720
1722
1724
1726
1728
1730
1732
1734
1736
1738
1740
1742
1744
1746
1748
1750
1752
1754
1756
1758
1760
1762
1764
1766
1768
1770
1772
1774
1776
1778
1780
1782
1784
1786
1788
1790
1792
1794
1796
1798
1800
1802
1804
1806
1808
1810
1812
1814
1816
1818
1820
1822
1824
1826
1828
1830
1832
1834
1836
1838
1840
1842
1844
1846
1848
1850
1852
1854
1856
1858
1860
1862
1864
1866
1868
1870
1872
1874
1876
1878
1880
1882
1884
1886
1888
1890
1892
1894
1896
1898
1900
1902
1904
1906
1908
1910
1912
1914
1916
1918
1920
1922
1924
1926
1928
1930
1932
1934
1936
1938
1940
1942
1944
1946
1948
1950
1952
1954
1956
1958
1960
1962
1964
1966
1968
1970
1972
1974
1976
1978
1980
1982
1984
1986
1988
1990
1992
1994
1996
1998
2000
2002
2004
2006
2008
2010
2012
2014
2016
2018
2020
2022
2024
2026
2028
2030
2032
2034
2036
2038
2040
2042
2044
2046
2048
2050
2052
2054
2056
2058
2060
2062
2064
2066
2068
2070
2072
2074
2076
2078
2080
2082
2084
2086
2088
2090
2092
2094
2096
2098
2100
2102
2104
2106
2108
2110
2112
2114
2116
2118
2120
2122
2124
2126
2128
2130
2132
2134
2136
2138
2140
2142
2144
2146
2148
2150
2152
2154
2156
2158
2160
2162
2164
2166
2168
2170
2172
2174
2176
2178
2180
2182
2184
2186
2188
2190
2192
2194
2196
2198
2200
2202
2204
2206
2208
2210
2212
2214
2216
2218
2220
2222
2224
2226
2228
2230
2232
2234
2236
2238
2240
2242
2244
2246
2248
2250
2252
2254
2256
2258
2260
2262
2264
2266
2268
2270
2272
2274
2276
2278
2280
2282
2284
2286
2288
2290
2292
2294
2296
2298
2300
2302
2304
2306
2308
2310
2312
2314
2316
2318
2320
2322
2324
2326
2328
2330
2332
2334
2336
2338
2340
2342
2344
2346
2348
2350
2352
2354
2356
2358
2360
2362
2364
2366
2368
2370
2372
2374
2376
2378
2380
2382
2384
2386
2388
2390
2392
2394
2396
2398
2400
2402
2404
2406
2408
2410
2412
2414
2416
2418
2420
2422
2424
2426
2428
2430
2432
2434
2436
2438
2440
2442
2444
2446
2448
2450
2452
2454
2456
2458
2460
2462
2464
2466
2468
2470
2472
2474
2476
2478
2480
2482
2484
2486
2488
2490
2492
2494
2496
2498
2500
2502
2504
2506
2508
2510
2512
2514
2516
2518
2520
2522
2524
2526
2528
2530
2532
2534
2536
2538
2540
2542
2544
2546
2548
2550
2552
2554
2556
2558
2560
2562
2564
2566
2568
2570
2572
2574
2576
2578
2580
2582
2584
2586
2588
2590
2592
2594
2596
2598
2600
2602
2604
2606
2608
2610
2612
2614
2616
2618
2620
2622
2624
2626
2628
2630
2632
2634
2636
2638
2640
2642
2644
2646
2648
2650
2652
2654
2656
2658
2660
2662
2664
2666
2668
2670
2672
2674
2676
2678
2680
2682
2684
2686
2688
2690
2692
2694
2696
2698
2700
2702
2704
2706
2708
2710
2712
2714
2716
2718
2720
2722
2724
2726
2728
2730
2732
2734
2736
2738
2740
2742
2744
2746
2748
2750
2752
2754
2756
2758
2760
2762
2764
2766
2768
2770
2772
2774
2776
2778
2780
2782
2784
2786
2788
2790
2792
2794
2796
2798
2800
2802
2804
2806
2808
2810
2812
2814
2816
2818
2820
2822
2824
2826
2828
2830
2832
2834
2836
2838
2840
2842
2844
2846
2848
2850
2852
2854
2856
2858
2860
2862
2864
2866
2868
2870
2872
2874
2876
2878
2880
2882
2884
2886
2888
2890
2892
2894
2896
2898
2900
2902
2904
2906
2908
2910
2912
2914
2916
2918
2920
2922
2924
2926
2928
2930
2932
2934
2936
2938
2940
2942
2944
2946
2948
2950
2952
2954
2956
2958
2960
2962
2964
2966
2968
2970
2972
2974
2976
2978
2980
2982
2984
2986
2988
2990
2992
2994
2996
2998
3000
3002
3004
3006
3008
3010
3012
3014
3016
3018
3020
3022
3024
3026
3028
3030
3032
3034
3036
3038
3040
3042
3044
3046
3048
3050
3052
3054
3056
3058
3060
3062
3064
3066
3068
3070
3072
3074
3076
3078
3080
3082
3084
3086
3088
3090
3092
3094
3096
3098
3100
3102
3104
3106
3108
3110
3112
3114
3116
3118
3120
3122
3124
3126
3128
3130
3132
3134
3136
3138
3140
3142
3144
3146
3148
3150
3152
3154
3156
3158
3160
3162
3164
3166
3168
3170
3172
3174
3176
3178
3180
3182
3184
3186
3188
3190
3192
3194
3196
3198
3200
3202
3204
3206
3208
3210
3212
3214
3216
3218
3220
3222
3224
3226
3228
3230
3232
3234
3236
3238
3240
3242
3244
3246
3248
3250
3252
3254
3256
3258
3260
3262
3264
3266
3268
3270
3272
3274
3276
3278
3280
3282
3284
3286
3288
3290
3292
3294
3296
3298
3300
3302
3304
3306
3308
3310
3312
3314
3316
3318
3320
3322
3324
3326
3328
3330
3332
3334
3336
3338
3340
3342
3344
3346
3348
3350
3352
3354
3356
3358
3360
3362
3364
3366
3368
3370
3372
3374
3376
3378
3380
3382
3384
3386
3388
3390
3392
3394
3396
3398
3400
3402
3404
3406
3408
3410
3412
3414
3416
3418
3420
3422
3424
3426
3428
3430
3432
3434
3436
3438
3440
3442
3444
3446
3448
3450
3452
3454
3456
3458
3460
3462
3464
3466
3468
3470
3472
3474
3476
3478
3480
3482
3484
3486
3488
3490
3492
3494
3496
3498
3500
3502
3504
3506
3508
3510
3512
3514
3516
3518
3520
3522
3524
3526
3528
3530
3532
3534
3536
3538
3540
3542
3544
3546
3548
3550
3552
3554
3556
3558
3560
3562
3564
3566
3568
3570
3572
3574
3576
3578
3580
3582
3584
3586
3588
3590
3592
3594
3596
3598
3600
3602
3604
3606
3608
3610
3612
3614
3616
3618
3620
3622
3624
3626
3628
3630
3632
3634
3636
3638
3640
3642
3644
3646
3648
3650
3652
3654
3656
3658
3660
3662
3664
3666
3668
3670
3672
3674
3676
3678
3680
3682
3684
3686
3688
3690
3692
3694
3696
3698
3700
3702
3704
3706
3708
3710
3712
3714
3716
3718
3720
3722
3724
3726
3728
3730
3732
3734
3736
3738
3740
3742
3744
3746
3748
3750
3752
3754
3756
3758
3760
3762
3764
3766
3768
3770
3772
3774
3776
3778
3780
3782
3784
3786
3788
3790
3792
3794
3796
3798
3800
3802
3804
3806
3808
3810
3812
3814
3816
3818
3820
3822
3824
3826
3828
3830
3832
3834
3836
3838
3840
3842
3844
3846
3848
3850
3852
3854
3856
3858
3860
3862
3864
3866
3868
3870
3872
3874
3876
3878
3880
3882
3884
3886
3888
3890
3892
3894
3896
3898
3900
3902
3904
3906
3908
3910
3912
3914
3916
3918
3920
3922
3924
3926
3928
3930
3932
3934
3936
3938
3940
3942
3944
3946
3948
3950
3952
3954
3956
3958
3960
3962
3964
3966
3968
3970
3972
3974
3976
3978
3980
3982
3984
3986
3988
3990
3992
3994
3996
3998
4000
4002
4004
4006
4008
4010
4012
4014
4016
4018
4020
4022
4024
4026
4028
4030
4032
4034
4036
4038
4040
4042
4044
4046
4048
4050
4052
4054
4056
4058
4060
4062
4064
4066
4068
4070
4072
4074
4076
4078
4080
4082
4084
4086
4088
4090
4092
4094
4096
4098
4100
4102
4104
4106
4108
4110
4112
4114
4116
4118
4120
4122
4124
4126
4128
4130
4132
4134
4136
4138
4140
4142
4144
4146
4148
4150
4152
4154
4156
4158
4160
4162
4164
4166
4168
4170
4172
4174
4176
4178
4180
4182
4184
4186
4188
4190
4192
4194
4196
4198
4200
4202
4204
4206
4208
4210
4212
4214
4216
4218
4220
4222
4224
4226
4228
4230
4232
4234
4236
4238
4240
4242
4244
4246
4248
4250
4252
4254
4256
4258
4260
4262
4264
4266
4268
4270
4272
4274
4276
4278
4280
4282
4284
4286
4288
4290
4292
4294
4296
4298
4300
4302
4304
4306
4308
4310
4312
4314
4316
4318
4320
4322
4324
4326
4328
4330
4332
4334
4336
4338
4340
4342
4344
4346
4348
4350
4352
4354
4356
4358
4360
4362
4364
4366
4368
4370
4372
4374
4376
4378
4380
4382
4384
4386
4388
4390
4392
4394
4396
4398
4400
4402
4404
4406
4408
4410
4412
4414
4416
4418
4420
4422
4424
4426
4428
4430
4432
4434
4436
4438
4440
4442
4444
4446
4448
4450
4452
4454
4456
4458
4460
4462
4464
4466
4468
4470
4472
4474
4476
4478
4480
4482
4484
4486
4488
4490
4492
4494
4496
4498
4500
4502
4504
4506
4508
4510
4512
4514
4516
4518
4520
4522
4524
4526
4528
4530
4532
4534
4536
4538
4540
4542
4544
4546
4548
4550
4552
4554
4556
4558
4560
4562
4564
4566
4568
4570
4572
4574
4576
4578
4580
4582
4584
4586
4588
4590
4592
4594
4596
4598
4600
4602
4604
4606
4608
4610
4612
4614
4616
4618
4620
4622
4624
4626
4628
4630
4632
4634
4636
4638
4640
4642
4644
4646
4648
4650
4652
4654
4656
4658
4660
4662
4664
4666
4668
4670
4672
4674
4676
4678
4680
4682
4684
4686
4688
4690
4692
4694
4696
4698
4700
4702
4704
4706
4708
4710
4712
4714
4716
4718
4720
4722
4724
4726
4728
4730
4732
4734
4736
4738
4740
4742
4744
4746
4748
4750
4752
4754
4756
4758
4760
4762
4764
4766
4768
4770
4772
4774
4776
4778
4780
4782
4784
4786
4788
4790
4792
4794
4796
4798
4800
4802
4804
4806
4808
4810
4812
4814
4816
4818
4820
4822
4824
4826
4828
4830
4832
4834
4836
4838
4840
4842
4844
4846
4848
4850
4852
4854
4856
4858
4860
4862
4864
4866
4868
4870
4872
4874
4876
4878
4880
4882
4884
4886
4888
4890
4892
4894
4896
4898
4900
4902
4904
4906
4908
4910
4912
4914
4916
4918
4920
4922
4924
4926
4928
4930
4932
4934
4936
4938
4940
4942
4944
4946
4948
4950
4952
4954
4956
4958
4960
4962
4964
4966
4968
4970
4972
4974
4976
4978
4980
4982
4984
4986
4988
4990
4992
4994
4996
4998
5000
5002
5004
5006
5008
5010
5012
5014
5016
5018
5020
5022
5024
5026
5028
5030
5032
5034
5036
5038
5040
5042
5044
5046
5048
5050
5052
5054
5056
5058
5060
5062
5064
5066
5068
5070
5072
5074
5076
5078
5080
5082
5084
5086
5088
5090
5092
5094
5096
5098
5100
5102
5104
5106
5108
5110
5112
5114
5116
5118
5120
5122
5124
5126
5128
5130
5132
5134